COST ESTIMATE

The cost estimate to remove the ACM in the Amtrak Station is provided in Table T-1.

TABLE T-1
ESTIMATED COST OF ABATEMENT OF ALL IDENTIFIED ACM

| RECOMMENDED ACTION | UNITS | UNIT COST | ESTIMATED COST* |
|---|------------|---------------|-----------------|
| Removal of 9" x 9" gray floor tile with white streaks | 1,294 s.f. | \$1.50/s.f. | \$1,941.00 |
| Removal of drywall joint compound (includes removal of drywall) | 3,000 s.f. | \$6.00/s.f. | \$18,000.00 |
| Removal of black sink undercoating | 1 ct. | \$100.00/each | \$100.00 |
| Removal of safe* | 2 ct. | \$100.00/each | \$200.00 |
| Removal of ceramic tile bedding compound* | 212 s.f. | \$5.00/s.f. | \$1,060.00 |
| Removal of black roof flashing | 10 l.f. | \$4.00/l.f. | \$40.00 |
| On-site air monitoring (asbestos) | 10 days | \$600.00/day | \$6,000.00 |

GRAND ESTIMATED TOTAL

\$27,341.00

The cost estimates are based on current industry prices. Industry prices may change at any time. It is assumed that the work is performed by licensed, competent organizations. Estimates include all costs of abatement projects except replacement. Estimated cost is based on project size, difficulty, access, and all work being done at one time, etc.

^{*}Sample these materials to determine their asbestos content, if any.